



Overview

- Enclosed IBC Bund - LH Configuration
- All Weather Polyethylene IBC Storage & Dispensing
- Enclosed IBC Bund solves many of the problems associated with IBC storage and chemical/fluid decanting in a weather-resistant, purpose-built enclosure.
- Easy forklift loading with wide forklift access from both side and back
- All cabinet doors can be locked to keep system secure
- 110% bund capacity complies with AS3780
- Venting x 2 sides
- Chemical resistant – high grade polyethylene construction



Capacity: 1,250L
Bund Volume: 1,453L (approx)
Dimensions LxWxH (mm): 1,690 x 1,895 x 2,445

Empty Weight: 320kg
IBC Camlock Connection: 40mm
TrackUnit GPS: Yes

Chemical Tank Datasheet

Tank Type	Enclosed IBC Bund	IBC Camlock Connection	40mm (1.5")
Material of Construction	PE	Maximum Specific Gravity Rating	2.0
No. of Roof Tie Down Lugs	4	Cabinet/Bund Drain Valve	DN15 PVC/FPM

Sustainability:

Carbon Neutral Organisation - Verified	Yes
Carbon Neutral Product - Verified	No
Power Consumption Reporting (kWh)	N/A

Associated Products:

- Trident Lamella Clarification Tank
- MudBug Tanks
- Kraken Filters
- Kraken Sludge
- Pumps

Associated Consumables:

- Coagulant
- Flocculant
- Acid/Caustic Solution

Note:

- Specification is subject to change without prior notice. Please check with your local Aquatic Engineering Australia representative for the latest specifications
- Flow/Treatment suitability is subject to inlet effluent water quality and required discharge parameters and is stated as a guide only